

## 1116 - KEL-PATCH SEALANT (SMOOTH)

### Acrylic Sealant and Patching Compound for Filling Cracks and Voids in Wood and Masonry

**PRODUCT DESCRIPTION**

A flexible acrylic elastomeric sealant for patching, caulking, resurfacing and filling cracks in stucco, concrete, masonry and wood. Features outstanding adhesion and flexibility.

**TYPICAL USES**

Sealing hairline cracks and filling voids in concrete, stucco, and masonry surfaces prior to painting. Resurfacing old, cracked wood surfaces prior to painting.

**LIMITATIONS**(Not to be construed as all-inclusive)

Not for use below grade. Not for use where patch will be under water. Not for use in control joints. For use only under conventional latex or elastomeric coatings.

**PRODUCT CHARACTERISTICS**

**SOLIDS:** Approximately 61% by volume.

**DRYING TIME:** (at 75°F. & 50% R.H.): To touch: 2 to 4 hours; top recoat: 24 hours.

**FINISH:** Flat.

**COLOR RANGE:** Off white.

**SIZES:** Five gallon pails and one gallon cans.

**SURFACE PREPARATION**

**GENERAL:** All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Etch glossy, glazed or dense surfaces.

**SPECIFICATIONS**

**PRIMERS:** None required on sound surfaces. Lightly chalking surfaces should be primed with 240 Kel-Bond Primer and Surface Conditioner or 225 Surface Conditioner.

**FINISH COATS:** Conventional latex or elastomeric coatings. See Kelly-Moore Systems Charts.

**PRODUCT HANDLING**

**APPLICATION:** Putty knife, brush or roller. Fill void completely leaving a slight crown to allow for shrinkage. Deep fills may require additional applications. Feather edges and remove excess material immediately.

**TEMPERATURE:** Do not apply when material, air, and/or surface temperature is below 50°F. or if rain is imminent within six hours. **PROTECT FROM FREEZING.**

**THINNING:** Apply at can consistency. Do not thin.

**CLEAN-UP:** Promptly with warm water.

**VOC:** Maximum 300 GPL.

**Limited Warranty**

The statements made on this bulletin, product label, or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, express or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.