

1124 - KEL-SEAL ELASTOMERIC TEXTURED ACRYLIC SEALANT

Textured Sealant for Cracks and Voids in Exterior and Interior Surfaces

PRODUCT DESCRIPTION

A heavy bodied acrylic textured sealant which features excellent adhesion and long term elasticity. It is designed for filling cracks and voids in similar and between dissimilar materials. For interior and exterior use.

TYPICAL USES

For filling cracks and voids in masonry and wood. Also for caulking between masonry, wood, and metal. Designed for primary or deeper fills under elastomeric finishes and for general caulking prior to application of conventional finishes.

LIMITATIONS

(Not to be construed as all-inclusive)
Normal shrinkage will require additional applications when filling larger joints. Not for submersion in water. Not for use as an expansion joint sealant. Not for cracks and voids larger than 1/4" by 1/4" deep.

PRODUCT CHARACTERISTICS

SOLIDS: Approximately 67% by volume.

DRYING TIME: (at 75°F. & 50% R.H.): To touch: 1/2 to 1 hour; to finish with latex paint: 1 to 2 hours; to finish with oil base paint: overnight. For deep joints and cracks allow 24 hours before reapplication.

ELONGATION: Approximately 525%.

COLOR: Off-white.

SIZES: 10.5 oz. cartridge.

SURFACE PREPARATION

GENERAL: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of this product.

PRODUCT HANDLING

APPLICATION: Clip plastic spout at an angle for the desired size bead. Puncture seal inside spout. Apply with caulking gun. Smooth bead if necessary and remove any excess material immediately.

TEMPERATURE: Do not apply when material, air, and/or surface temperature is below 50°F. or if rain is imminent within six hours. PROTECT FROM FREEZING.

Limited Warranty

The statements made on this bulletin, product label, or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, express or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.